

# 947H

## SINOMACH

## SINOMACH-HI INTERNATIONAL EQUIPMENT CO.,LTD.

Rated Power:132kW@2200rpm

Operating Weight:12300kg      Rated Bucket Capacity:2.3m<sup>3</sup>



- Equipped with Dongfeng Cummins engine,
- Luxury cabin decoration and A/C provide operator comfort,
- 4 forward & 3 reverse power shift transmission,
- Combined seal cylinder obtains high seal performance and more reliability.



国机重工集团国际装备有限公司  
SINOMACH-HI INTERNATIONAL EQUIPMENT CO.,LTD.

# 947H WHEEL LOADER MAIN SPECIFICATIONS



## 发动机 Engine

型号	康明斯 6BTAA5.9-C180
Model	Cummins 6BTAA5.9-C180
型式	直喷, 涡轮增压, 水冷
Type	Direct injection. Turbocharged. Water cooling
额定功率 Rated Power	132kW
额定转速 Rated Speed	2200rpm/min
最低燃油消耗率 Min.fuel Consumption	≤212g/kW.h
最大扭矩 Max.Torque	750N.m



## 变速系统 Transmission System

变矩器型式	四元件, 双级
Torque converter type	4-elements.double stage
冷却方式	油冷压力循环式
Cooling ways	Oil cooling. pressure circulating
变速箱型式	定轴式动力换挡
Transmission type	Fixed shaft-power shift
档位 (前进档/后退档)	前四后三
Shifts(Forward/reverse)	F4/R3
前进行驶速度 km/h	6.5 12 25 35
Forward traveling speed	
后退行驶速度 km/h	6.5 12 25
Reverse traveling speed	



## 驱动桥和主传动 Axles and Main Drive

驱动系统	四轮驱动
Drive system	Four-wheel diving
前后桥主传动型式	螺旋伞齿轮一级减速
Main drive type	One spiral bevel gear. stillge, one-stage
减速比 Gear ratio	5.286
轮边减速型式	单级行星轮
Hub reduction	Single stage planetary
减速比 Gear ratio	4.26
最大爬坡能力 Max. grade ability	25°



## 工作装置 Work Equipment

卸高 (45° 卸载角度)	3176mm
Dumping clearance (at dumping angle 45°)	3176mm
卸距 (45° 卸载角度)	1095mm
Dumping reach (at dumping angle 45°)	1095mm

SINOMACH-HI INTERNATIONAL EQUIPMENT CO.,LTD.

Add:No.898,Huanghe Road(West),Changzhou City,  
Jiangsu Province,China.

P.C:213136

Tel:86-519-86781288 86752400

Fax:86-519-86781387

[Http://www.sinomach-hi.com](http://www.sinomach-hi.com)

E-mail:sales@changlin.com.cn service@changlin.com.cn



## 转向系统 Steering System

型式	车架铰接, 全液压转向
Type	Middle articulated frame. Full-hydraulic Steering
转向角 Steering angle	±38°
最小转弯半径 Min.steering radius	6300mm
转向油缸数-缸径×行程 Steering cylinders inner Bore × Stroke	2-Φ80×327mm
工作压力 Operation pressure	14MPa



## 制动系统 Brake System

脚制动型式: 气顶油, 钳盘式四轮制动  
Travel brake type over hydraulic caliper disc brake,  
activate 4-wheel brake  
手制动型式: 手动控制断气制动  
Service brake type: Manual control cutting-off air brake



## 工作液压系统 Working Hydraulic System

型式 Type	软轴操纵(可选装单手柄先导操纵)
油缸数量-缸径×行程 No. of Cylinders-Bore × Stroke	
举升油缸 Lift cylinder	2-Φ125×771mm
翻斗油缸 Dump cylinder	1-Φ188×502mm
系统工作压力 System operation pressure	18MPa
提升时间 Lifting time	5.5s
下降时间 Lowering time	3.2s
卸载时间 Dumping time	1.1s



## 轮胎 Tyre

根据工作情况选择合适轮胎  
Choose suitable tyre according to situations  
标准车 Standard tyre.....20.5-25-16PR



## 再注容量 Refill Capacity

燃油箱 Fuel tank	150L
发动机曲轴箱 Engine crank case	13L
液力变矩器和变速箱 T/C and Transmission	45L
液压油箱 Hydraulic tank	150L
前后桥主传动 Axles main drive	2×24L
制动系统 Brake system	2×1L

DEALER: